



# QUICK GRAB

**QUICK GRAB** is a high strength instant adhesive based on cyanoacrylates. It does not contain any solvents.

## PHYSICAL AND TECHNICAL PROPERTIES

**Colour:** Clear

**Density :** 1,10 gr/cm<sup>3</sup>

**Temperature variation resistance :** -20°C to + 80°C

**Curing speed :** 5 - 40 sec

**Tensile strength :** 200 Kg/cm<sup>2</sup>

**Viscosity :** 40 – 60 cps

**Adhesion:** Excellent adhesion on a big variety of porous as well as non-porous substrates without primer.

## APPLICATION FIELDS

QUICK GRAB is suitable for all bonding applications where a precise, instant and strong bond is required. It provides excellent adhesion, on metals, plastics, wood, glass, ceramics, rubber, leather, etc. **It is especially suitable for gluing EPDM rubber in aluminum window frames.** Can be used in DIY or professional applications.

## APPLICATION INSTRUCTIONS

**Substrate :** The substrate must be free of dust, oil or water. No primer is generally required.

**Application :** Put on one part a small amount of glue with the special brush. Usually one drop is enough. Bring the two parts together and wipe off the excess glue with a suitable cloth. Hold the bonded parts together for 20 – 40 seconds. The curing speed can vary according to the quantity of the glue applied and the type of the substrate. The final strength of the adhesive will be achieved several hours after the application.

**Cleaning of tools, parts and hands:** The material can be wiped off with a cloth soaked in acetone or nail polish remover.

## SHELF LIFE

QUICK GRAB can be stored for at least 12 months after the production date.



### **Warning to users**

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELASTOTET GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELASTOTET is at their disposal to supply any additional information.